

5 wt.% iron oxide on silica H₂S conversion ■3rd. □4th Selectivity tv S.●3rd,O4th

Fig. 1




Fig. 28






Fig. 3

FIG. 48





Fe/Zn FerZn catalyst

Property of the control of the second

Temperature (C*)

3/3

ire (C')

Temperature (C')

a) Fe(5)Zn(10)Si-Cl. (5 wt. 70 Fer Oz/10 wt. 70 ZnO on silicate, with Cl)

b) Fe(5)Zn(10)Si. (5 wt. 20 Fer Oz/10 wt. 70 ZnO on silicate, with Cl)

wheret-Cl)

5 wt.% iron oxide on silica H₂S conversion ■ 3rd. □ 4th Selectivity tv S. 3rd, 4th

Fig. 4





Fig. 5



5 wt.% iron oxide on silica H₂S conversion ■3rd. □4th Selectivity tv S.●3rd,O4th

Fig. 1




Fig. 2





Fig. 3

.



Fe₇Zn catalyst

a) Fe(5)Zn(10)Si-Cl.

b) Fe(5)Zn(10)Si.

5 wt.% iron oxide on silica H₂S conversion ■ 3rd.□ 4th Selectivity tv S.● 3rd,○ 4th

Fig. 4




Fig. 5